


CLOPAY COMMERCIAL – MODELS 3200, 3211, 3213

energy series



Model 3200, 32'2" x 14 door, shown with 24" x 8" Lites

CONSTRUCTION	STEEL	EFFICIENCY	WARRANTY
2" THICKNESS	24 GAUGE	9.1 R-VALUE	10YR LIMITED CONSTRUCTION

POLYSTYRENE INSULATED STEEL DOORS

Clopay Models 3200, 3211 and 3213 are high quality doors designed for commercial and industrial facilities and provide the durability of a full 24 gauge, heavy-duty exterior steel skin in an energy efficient door system.

- **Polystyrene Insulation** provides comfort, energy efficiency and quiet operation in every season.
- **Steel-Sandwich Construction** enhances durability and strength.
- **3-Stage Paint Process** delivers a maintenance-free finish.
- **Thermal Break** enhances insulating properties for extreme energy efficiency.
- **Optional Accessories** add functionality while complementing the building.

clopaycommercial.com




Panels are pre-painted inside and out to inhibit rust. Hot-dipped, galvanized steel is painted with primer and given a tough oven-baked polyester top coat to provide the most rust-resistant steel door available. Ten-year warranty against rust-through.

PANEL DESIGNS



COLOR OPTIONS

MODEL 3200



ADDITIONAL COLORS FOR MODELS 3211, 3213



* Not available on Models 3211 and 3213.
Due to the printing process, colors may vary.

CUSTOM PAINT OPTION



Color Blast™ offers more than 1,500 Sherwin-Williams® color options to complement your building design. Clopay's durable factory finish has been thoroughly tested and is backed by a five-year warranty.

FEATURES

STANDARD HARDWARE

- 18 gauge single-end stiles; 16 gauge double-end stiles
- PVC vinyl astragal with aluminum retainer
- Commercial 10-ball steel rollers (nylon tires available)
- Steel step plate and lift handle
- Heavy-duty galvanized end stiles
- Inside slide lock for increased security
- 19 gauge steel hinge support plates
- 2" (50.8 mm) or 3" (76.2 mm) track
- 10,000 cycle springs
- Galvanized aircraft cable with minimum 7:1 safety factor
- Variety of track configurations to meet building specifications

MATERIALS AND CONSTRUCTION

Panel Thickness	2" (50.8 mm)
Insulation	2" (50.8 mm) Polystyrene
R-value	9.1*
Thermal Break	Continuous silicone filled
Exterior Steel	24 gauge (.023" min.) (.58 mm)
Interior Steel	28 gauge (.015" min.) (.38 mm)
Exterior Surface	Stucco embossed, minor ribbed (3200) Woodgrain embossed, flush (3211) Woodgrain embossed, elegant raised (3213)
Max Width	3200: 32'2" (9.8 m); 3211/3213: 24'2" (7.4 m)
Max Height	3200: 24' (7.3 m); 3211/3213: 18' (5.5 m)
Exterior Colors	Standard White, Almond, Desert Tan, Sandtone, Commercial Tan, Brown, Black, Hunter Green, Gray, Trinar® White and Trinar® Beige. Also available in Color Blast™.
Interior Color	Standard White
Limited Warranties	10-Year delamination 10-Year rust-through 1-Year material and workmanship

*Calculated door section R-value is in accordance with DASMA TDS-163.

For special sizes, applications and options, consult Commercial Information Assistance (CIA) at 1-800-526-4301.




For more information on these and other Clopay products, call 1-800-526-4301 or visit clopaycommercial.com



©2015 Clopay Building Products Company, Inc., a Griffon company.


ADDITIONAL OPTIONS

WINDOW OPTIONS



Model 3200 is available with nominal insulated glass, nominal insulated tempered glass or tempered glass. Full vision section, pre-painted standard white or brown; glazing options include DSB, plexiglass, wire and insulated glass. Models 3211 and 3213 are available with DSB, plexiglass and insulated glass.

HEAVY-DUTY HARDWARE (where not standard)



Double-end hinge

3" Track

Outside keyed lock

HIGH CYCLE SPRINGS



25,000, 50,000 or 100,000 cycle springs available.

MULLIONS



Carry-away, roll-away or swing-up mullions are available on select sizes.

BREAK-AWAY SECTION



Single section and double sections available on select sizes.

PASS DOOR



32" wide x 80" high (.81 m x 2.3 m), max 16'2" (4.9 m) wide section.

EXHAUST PORT



Can be cut into any type of sectional door. Available in select sizes.



WindCode® doors are available in many sizes and pressure ratings.



Upgrade your standard door with industrial-grade components.

DISTRIBUTED BY:

